


FIG. 1

FORCE ACTS ON NEUTRAL ATOM (SCATTERING FORCE)


•LIGHT ABSORPTION OF ATOM IN MOTION WITH CONSTANT VELOCITY




$$v_L = v_0 \cdot c / (c + v_0)$$

$$= v_0 \cdot \{1 - v_0 / (c + v_0)\}$$

$$< v_0$$



•LIGHT EMISSION OF ATOM IN MOTION WITH CONSTANT VELOCITY



$$F = \Delta P / (2\tau) = M(v_0 - v_1) / (2\tau)$$

$$= h v_L / (2\tau c)$$




FIG. 2

STOP TIME

$$t = 2N\tau = 2 \cdot 11476 \cdot 5.524861878\text{ns} = 126.8 \mu\text{s}$$

NATURAL WIDTH

$$\Delta\nu (= \gamma) = 1/(2\pi\tau) = 1/(2 \times 3.141592654 \times 5.52486\text{ns}) = 28.807054\text{MHz}$$

Doppler COOLING TEMPERATURE

$$k_{TD} = h/(2\pi) \cdot \gamma = 6.6260755 \times 10^{-34} / 2 / 3.141592654 / (2 \times 3.141592654 \times 5.52\text{ns}) = 220.227 \mu\text{K}$$

FIG. 3

Doppler WIDTH

$$\Delta \nu_d = 2\nu_0 \left(\frac{2k_B T}{Mc^2} \right) \ln 2)^{1/2} = 2 \cdot 1.18735651 \times 10^{15} \cdot (2 \times 1.380658 \times 10^{-23} \times 27.976957 \cdot 1.6605402 \times 10^{-27} \times 2.99792458 \times 10^8 \times 2.99792458 \times 10^8) \cdot \ln 2)^{1/2} = 160.7815759 \cdot T^{1/2} \text{ MHz}$$

IN GASEOUS MOLECULE IN THERMAL EQUILIBRIUM, ATOMS EXHIBIT IRREGULAR BROWNIAN MOVEMENT, EACH ATOM POSSESSES SLIGHTLY DIFFERENT RESONANCE FREQUENCY FROM ONE ANOTHER, AND POSSESSES NATURAL WIDTH IN EACH ATOM.

ACCORDINGLY, AS IN CASE OF GASEOUS MOLECULE, ENVELOPE IN SPECTRAL DISTRIBUTION OF SPONTANEOUS EMISSION REFLECTS ON DISPERSION IN CENTER FREQUENCY OF EACH ATOM. SUCH BROADENING IS CALLED BY NAME OF INHOMOGENEOUS BROADENING.

$$\text{Doppler WIDTH AT MELTING TEMPERATURE } 6045.9 \text{ MHz} = 6.0459 \text{ GHz}$$

FIG. 4(a)




FIG. 4(b)

$$\begin{aligned}\frac{dN_u}{dt} &= W_{\sigma+} + W_{\pi} + W_{\sigma-} - \frac{N_u}{\tau} \\ \frac{dN_{g,-1}}{dt} &= -W_{\sigma+} + \frac{N_u}{3\tau} \\ \frac{dN_{g,0}}{dt} &= -W_{\pi} + \frac{N_u}{3\tau} \\ \frac{dN_{g,+1}}{dt} &= -W_{\sigma-} + \frac{N_u}{3\tau}\end{aligned}$$

FIG. 4(c)




FIG. 5




FIG. 6

BIREFRINGENCE CRYSTAL

n_o : REFRACTIVE INDEX IN ORDINARY RAY

n_e : REFRACTIVE INDEX IN EXTRAORDINARY RAY

WHERE $n_o < n_e$ (PHASE DELAYS IN n_e -AXIS)

$$\Phi = 2 \pi (n_o - n_e) d / \lambda$$





FIG. 7



TIME REQUIRED FOR ABSORPTION - EMISSION
OF ONE PHOTON

$$: 2\tau = 11\text{ns} \quad (\tau = 5.5\text{ns})$$



IT IS EFFICIENT WHEN NEXT PHOTON STRIKES AFTER 11 ns

$$\text{PERIOD } 11\text{ns} \times 4 = 44\text{ns}$$



FREQUENCY IN PHASE
MODULATOR

$$f_m < 22.7\text{MHz}$$





FIG. 8(a)


POLARIZED LIGHT CONTROL BY THREE COHERENT LIGHT SOURCE DEVICES



NO SIMULTANEOUS EMISSION

COHERENT EFFECT APPEARS SO THAT EFFICIENT COOLING
CANNOT BE MADE


FIG. 8(b)



OPTIMUM IS TWO TIMES LONGER THAN LIFETIME OF SPONTANEOUS EMISSION
(11 ns IN CASE OF SILICON)

FIG. 9(a)

POLARIZED LIGHT CONTROL BY TWO COHERENT LIGHT SOURCE DEVICES



NO SIMULTANEOUS EMISSION

COHERENT EFFECT APPEARS SO THAT EFFICIENT COOLING
CANNOT BE MADE

FIG. 9(b)





FIG. 10


PICOSECOND COHERENT LIGHT SOURCE FOR SILICON DECELERATION: 252.4 nm WAVELENGTH



378 nm CORRESPOND TO SECOND HARMONICS OF 757 nm,
AND 252.4 nm CORRESPOND TO THIRD HARMONICS OF 757 nm

FIG. 11


PICOSECOND COHERENT LIGHT SOURCE FOR SILICON DECELERATION: 252.4 nm WAVELENGTH



504.8 nm CORRESPOND TO SECOND HARMONICS OF 1009.6 nm,
AND 252.4 nm CORRESPOND TO SECOND HARMONICS OF 504.8 nm

FIG. 12

PICOSECOND COHERENT LIGHT SOURCE FOR SILICON DECELERATION TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 252.4 nm WAVELENGTH



378 nm CORRESPOND TO SECOND HARMONICS OF 757 nm,
AND 252.4 nm CORRESPOND TO THIRD HARMONICS OF 757 nm

1911 12 11, 15 16 River George St. in High St. Place
 under Ward's Ward's Ward's Ward's Ward's Ward's
 1911 12 11, 15 16 River George St. in High St. Place
 under Ward's Ward's Ward's Ward's Ward's Ward's

WAVELENGTH DISPERSION ELEMENT
(PRISM, GRATING, MULTILAYER
MIRROR, FILTER) 104' 110'

SECOND WAVELENGTH CONVERSION ELEMENT

**MODE-LOCKED
(LOCK)
PICOSECOND
LASER**

FREQUENCY- CONTROLLING ERROR SIGNAL GENERATOR

**FREQUENCY
CONVERTER**
 $f \rightarrow \sim f/4$

504.8 nm CORRESPOND TO SECOND HARMONICS OF 1009.6 nm, AND 252.4 nm CORRESPOND TO SECOND HARMONICS OF 504.8 nm





FIG. 14

CW COHERENT LIGHT SOURCE FOR SILICON DECELERATION/COOLING TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 252.4 nm WAVELENGTH



SILICON DECELERATION: FREQUENCY IS CHANGED TIME-VARYINGLY BY USE OF

ACOUSTO-OPTIC DEVICE (CHIRPED COOLING)

SILICON COOLING: ACOUSTO-OPTIC DEVICE HAS EFFECT FOR SEPARATING POLARIZED LIGHT AND ADVANTAGEOUS FOR OPTIMIZING FREQUENCY

THERE IS CASE EFFECTIVE FOR CHIRPED COOLING BY INCREASING FREQUENCY SHIFT AMOUNT WITH ADDITION OF ELECTRO-OPTIC SHIFTER (EO SHIFTER)

FIG. 15




FIG. 16




FIG. 17





FIG. 18


PICOSECOND COHERENT LIGHT SOURCE FOR GERMANIUM
DECELERATION: 271 nm WAVELENGTH



406.5 nm CORRESPOND TO SECOND HARMONICS OF 813 nm,
AND 271 nm CORRESPOND TO THIRD HARMONICS OF 813 nm

FIG. 19

PICOSECOND COHERENT LIGHT SOURCE FOR GERMANIUM
DECELERATION: 271 nm WAVELENGTH



542 nm CORRESPOND TO SECOND HARMONICS OF 1084 nm,
AND 271 nm CORRESPOND TO SECOND HARMONICS OF 542 nm

PICOSECOND COHERENT LIGHT SOURCE FOR GERMANIUM DECELERATION TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 271 nm WAVELENGTH




406.5 nm CORRESPOND TO SECOND HARMONICS OF 813 nm,
AND 271 nm CORRESPOND TO THIRD HARMONICS OF 813 nm.

FIG. 21

PICOSECOND COHERENT LIGHT SOURCE FOR GERMANIUM DECELERATION TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 271 nm WAVELENGTH


PULSE WIDTH 1ps~1000ps
(FREQUENCY WIDTH
1000 GHz TO 1 GHz
IN PULSES OF Fourier
TRANSFORM-LIMIT)



542 nm CORRESPOND TO SECOND HARMONICS OF 1084 nm,
AND 271 nm CORRESPOND TO SECOND HARMONICS OF 542 nm

CW COHERENT LIGHT SOURCE FOR GERMANIUM DECELERATION/COOLING TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 271 nm WAVELENGTH

CW COHERENT LIGHT SOURCE FOR GERMANIUM DECELERATION/COOLING TO WHICH POLARIZED LIGHT CONTROL FUNCTION HAS BEEN ADDED: 271 nm WAVELENGTH



GERMANIUM DECELERATION: FREQUENCY IS CHANGED TIME-VARYINGLY BY
USE OF ACOUSTO-OPTIC DEVICE (CHIRPED COOLING)

GERMANIUM COOLING: ACOUSTO-OPTIC DEVICE HAS EFFECT FOR SEPARATING POLARIZED
LIGHT AND ADVANTAGEOUS FOR OPTIMIZING FREQUENCY

THERE IS CASE EFFECTIVE FOR CHIRPED COOLING BY INCREASING
FREQUENCY SHIFT AMOUNT WITH ADDITION OF ELECTRO-OPTIC SHIFTER (EO SHIFTER)